



Identification

Ⓐ-Ⓑ-Ⓒ-Ⓓ

- Ⓐ Product name
- Ⓑ Dimension Width, mm
- Ⓒ Dimension Height, mm
- Ⓓ Inductance, 8R2 = 8.2μH

Series No.	A	B	C	D1	D2	1	2	3	Specifications
SPEM-040-20	4.0±0.2	4.1±0.2	2.0 max	1.5±0.3	0.8±0.3	2.2	2.5	5.2	Click
SPEM-050-30	5.1±0.2	5.5±0.2	3.0 max	1.5±0.3	1.0±0.3	3.0	2.5	7.0	Click
SPI-070-24	6.6±0.2	7.0±0.2	2.4 max	3.0±0.2	1.27±0.3	3.8	3.5	7.4	Click
SPI-070-30	6.6±0.2	7.0±0.2	3.0 max	3.0±0.2	1.27±0.3	3.8	3.5	7.4	Click
SPIP-070-40	6.6±0.2	7.0±0.2	4.0 max	3.0±0.2	1.27±0.3	3.8	3.5	7.4	Click
SPIP-070-60	6.6±0.2	7.0±0.2	6.0 max	3.0±0.2	1.27±0.3	3.8	3.5	7.4	Click
SPI-080-40	8.1±0.2	8.64±0.2	4.0 max	3.0±0.2	1.27±0.3	3.8	3.5	7.4	Click
SPI-080-65	8.1±0.2	8.64±0.2	6.5 max	3.0±0.2	1.27±0.3	3.8	3.5	7.4	Click
SPI-100-40	10.0±0.4	10.7±0.4	4.0 max	4.0±0.2	2.2±0.3	5.5	4.4	12.6	Click
SPI-100-50	10.0±0.4	10.7±0.4	5.0 max	4.0±0.2	2.2±0.3	5.5	4.4	12.6	Click
SPI-100-70	10.0±0.4	10.7±0.4	7.0 max	4.0±0.2	2.2±0.3	5.5	4.4	12.6	Click
SPI-130-40	12.7±0.3	13.2±0.4	4.0 max	3.0±0.3	2.0±0.5	8.0	3.5	14.8	Click
SPI-130-50	12.7±0.3	13.2±0.4	5.0 max	3.0±0.3	2.0±0.5	8.0	3.5	14.8	Click
SPI-130-65	12.7±0.3	13.2±0.4	6.5 max	3.0±0.3	2.0±0.5	8.0	3.5	14.8	Click
SPI-150-85	15.0±0.3	16.0±0.4	8.5 max	7.5±0.3	3.5±0.5	8.5	8.5	16.5	Click
SPI-170-75	17.15±0.3	18.0±0.3	7.5 max	12.0±0.2	2.5±0.4	11.4	12.2	18.9	Click
SPI-220-130	22.2±0.4	23.1±0.4	13.0 max	18.5±0.3	4.8±0.4	12.6	18.8	24.0	Click